

REFERENCE

HAZARDOUS CHEMICAL - STOCK

<u>Description</u>	<u>Quantity</u>	<u>Classification</u>
Alcohol, USP: 1-pt can	50	Flammable
Alcohol, USP: 5-gal. drum (Ethanol Ethyl Alcohol)	54	Flammable
Isopropyl Rubbing Alcohol: USP: 1-pt bottle	200	Flammable
Developing Solution, Direct Electrostatic Process: Power Form: 25-1b package; S/E Zeroz SR54	9	Skin Irritant
Developer, Photographic: 2.5 liter bottle	672	Skin Irritant
Developer, Photographic: 2.5 liter bottle: Kodak MX-819 Additive Part B	5	Skin Irritant
Developer, Photographic: Powder Form; Single Unit for Mixing; 1 gal. yield Kodak D-19 Developer Cat.146 4593	155	Skin Irritant
Developer, Photographic: Powder Form Single Unit for Mixing; 1 gal. yield Kodak D-76 Developer	232	Skin Irritant
Developer, Photographic; Powder Form; Single Unit for Mixing 1 gal. yield; Kodak Dektol; Mil-D-4827	167	Skin Irritant
Developer, Photographic: Powder form: Single unit for mixing: 1 qt yield	99	Skin Irritant
Developer, Photographic: Powder form: single unit for mixing: 32 oz yield	82	Skin Irritant
Developer, Photographic: Powder form: Single unit for mixing: 1 gal yield	26	Skin Irritant
Wetting Agent: Liquid Form: 16 oz bottle: water dispersing medium, (Kodak F filter-flo 200) FED SPEC 0-W-221	167	Skin Irritant

Attachment B

Stop Bath, Photographic: liquid Form: Single unit for mixing: 8 gal yield, 16 oz bottle; Kodak indicator stop	36	Skin Irritant
Activator, photographic: liquid form; premixed; 16 oz bottle 3M print activator	146	Skin Irritant
Developer, photographic: powder form; single unit for mixing; 5 gal yield	199	Skin Irritant
Fixing bath, photographic; powder form single E unit for mixing; 1 gal yield	470	Skin Irritant
Developer, Photographic; powder form; single unit for mixing, 1 gal yield	44	Skin Irritant
Developer, Photographic: liquid; premixed, 2 1/2 gallon	24	Skin Irritant
Stabilizer, photographic: 2 1/2 gallon size	40	Skin Irritant
Developing solution, Diffusion transfer process: liquid form: premixed unit; 1.1. kilogram	36	Skin Irritant
Developer, photographic: powder form, 14 lb package	120	Skin Irritant
Electrolyte, Bt Bottle 1.700	494	Corrosive
Ethyl Ether, Anhydrous, ACS: Liquid form; 4-lb can; 99 PCT Ethyl Ether, FED SPEC 0-C-265	6	Flammable liquid
Toluene, Technical; liquid form, 3 oz can; distillation temp 109 deg C initial boiling point and 113 deg c dry; gravity value 0.872, FED SPEC TT-T-548	14	Flammable liquid
Cylinder, nitrogen, lecture; filled	13	Non-Flammable compressed Gas
Insect repellent, personal application; 65 pct 2-Ethylhexanediol-1.3; 22 pc T Stearic acid; 11 pct Ozokerite 871 wax; 2 pct inert ingredients, stick fo rm; 1 oz size	282	Mildly Irritant to skin

Insect and Leech Repellent, Clothing and Personal Application; 75 pct Diethyltoluamide in ethanol; 2 oz polyethylene bottle; type II; size A, Concentration A; FED SPEC 0-1-503	12	Flammable liquid
Insecticide, D-Phenothrin; 12 oz aerosol can	149	Non-Flammable liquid compressed gas
Cleaning compound, solvent-detergent; detergent and wetting agent; alconox-aloe No. L-29706	1	Skin Irritant
Cleaning and Lubricating compound, electrical contact; heavy duty contact Cleaner & Lubricant, aerosol can, 16 oz, G C Electronics 10-1008	192	Non-Flammable Comp gas
Methylene Chloride; low grade; four litter or gallon safety container	59	This is a regulated item Class ORM-A (Other regulate material Class-A)
Cleaner and Lubricant set; for cleaning recording heads on magnetic tape recorders; c/o red solution used as a cleaner to remove dirt & oxide coating (2 oz bt) and blue solution used as a lubricant for application to the tape guides & recording heads; S/E EMC Recording Corp. 'Long Life' cleaner	92	Flammable liquid
Toner; 500 gm; f/u/w ESDA	32	Skin Irritant
Toner, direct electrostatic process, powder form; premixed unit; 2 lb package; Xerox p/n 6R57	148	Skin Irritant
Toner, Indirect Electrostatic Processing; liquid form; premixed unit; 43 oz bottle, Dennison P/N 09-006	55	Skin Irritant
Cleaning compound, solvent; solution type; 1 gal drum, Ray-Proof Corp; p/n CL-100	11	Skin Irritant
Toner, direct electrostatic process (powder form); xerox p/n 6R157	4	Skin Irritant
Toner, Direct Electrostatic process; powder form, Hunt Universal 36	246	Skin Irritant

Approved For Release 2003/11/06 : CIA-RDP85-00988R000600210006-8

Developer, indirect electrostatic process; powder form, single unit for mixing; 24 lb package; f/u/w Xerox model 4000 copier; Xerox 5R37	32	Skin Irritant
Toner, direct electrostatic process; powder form, 2 gal carton, Xerox p/n 6R178	192	Skin Irritant
Toner and Dispersant kit; c/o one 3.33 oz bottle toner concentrate and six 32 oz bottles of dispersant, p/n 92-2085	15	Skin Irritant
Toner, direct electrostatic process; liquid form; premixed unit; 2.016 gal per pkg, Dennison 09-014	22	Skin Irritant
Toner, Direct electrostatic process; powder form; premixed; 4 oz can Xerox 6R173	14	Skin Irritant
Toner, clear; six 1 qt bottles per box, f/u/w Saxon PPC-1 Copier; Saxon P/N 200200	11	Skin Irritant
Toner, direct electrostatic process; powder form, premixed unit 250 grams per bottle; Dennison p/n 09-44-3	12	Skin Irritant
Toner, direct electrostatic process; powder form; premixed unit, 1.5 pounds per cartridge; Nashua p/n IT-2	42	Skin Irritant
Toner, direct electrostatic process; powder form; ten 8 oz bottles per carton, Nashua 7AP	83	Skin Irritant
Toner, direct electrostatic process; liquid form; premixed unit, 32 oz bottle, OCE 213550	30	Skin Irritant
Duplicating Fluid, direct process; high methol alcohol type 1 gal can; type 2; SPEC O-D-825; IBM A-27	10	Flammable liquid
Paint, oil; red-lead paint, ready mixed with linseed oil base for priming or coating iron or steel, FED SPEC TT-D-86	48	Flammable liquid
Lacquer, acrylic resin or cellulosic derivative; gray, 1-pt pressurized spray can; 13 pct min nonvolatile material	114	Flammable gas
Lacquer; acrylic nitrocellulose; Fed Std 595, 16 oz pressurized spray can; 9 pct minimum nonvolatile material	114	Flammable gas

Approved For Release 2003/11/06 : CIA-RDP85-00988R000600210006-8

Sealing compound, 0.315 liter tube, f/u/w standard caulking gun; semipaste; General Electric SCS 1202	65	Skin Irritant
Adhesive, resin, semiliquid form; w/separate catalyst, 4.000 GM pkg, Hardman Inc 8173	11	Skin Irritant
Adhesive, liquid form; 4 oz bottle, (pure gum mucilage); SPEC MM-M792	24	Flammable liquid
Grease, Ball and Roller Bearing, mineral oil, calcium soap, and sodium; 4 oz tube; Stewart Warner p/n 38	53	No Class
Lubricating oil, general purpose, 16 oz spray bottle, Ray Proof Corp 1b-100	68	Non Flammable gas

Fuser Oil; 61 oz plastic container, Xerox No. 8R-79	266	Skin Irritant
Lubricating Oil, General Purpose; 32 oz can, Western Electric KS-7470; Teletype Corp 88970	87	No Class
Grease, synthetic, lubricant; diester-based, 4 oz tube; Tenneco Inc Anderol 795	3	No Class

STAT

Approved For Release 2003/11/06 : CIA-RDP85-00988R000600210006-8